

T&J ELECTRIC (SINGAPORE) PTE LTD

Company Registration No: 200205797Z
10 Ubi Crescent, #02-24, Ubi Techpark, Singapore 408564
Telephone: +65 6547-4333 Fax: +65 6547-4666

Date: 26/9/2013

Subject: TM-020056 : Product Info Radiance Retractive Switches

Overview:

Features

- 5mm ultra thin - streamlined contact surface.
- Made from premium quality polycarbonate and top grade PA66 Nylon.
- It is fire and heat resistant, durable and shockproof.
- Rocker bounce back to normal position after press

Technical Data:

- Rated Voltage: 250V a.c. 50Hz
- Rated Current:
16AX - Fully rated for fluorescent and inductive load.
- No. of cores to each Terminal hole:
5 x 1mm²
4 x 1.5mm²
3 x 2.5mm²
2 x 4mm²
- Gap between Contact: 3mm nominal
- Contact Material: Ag-Ni Alloy
- Operating Temperature: -5°C to +40°C
- IP Rating: IP4X
- Dimensions:
86 x 86 mm (1-4 Gang)
86 x 146 mm (5 Gang)
- Fix Center:
60.3 mm (1-4 Gang)
120.6mm (5 Gang)
- Fix Screws: M3.5 x 18 mm
- No. of operations :
40,000 operation at 16 Amp
- Comply to standards:
BS EN 60669
SS 227 with Safety Mark Approval
MS 616 with SIRIM mark



T&J ELECTRIC (SINGAPORE) PTE LTD

Company Registration No: 200205797Z
10 Ubi Crescent, #02-24, Ubi Techpark, Singapore 408564
Telephone: +65 6547-4333 Fax: +65 6547-4666

Date: 26/9/2013

Subject: TM-020056 : Product Info Radiance Retractive Switches

Package

- Pack Size: 10 pcs 1-4 Gang
5 pcs 5 Gang
- Carton Size: 100 pcs 1-4 Gang
50 pcs 5 Gang

Mounting Box

- 25mm depth or higher.
B1125 (surface) 1-4 Gang
B1125D (surface) 5 Gang
M1025 (flush) 1-4 Gang
M1025D (flush) 5 Gang

Wiring Circuit

